

Wrap-around woven sleeving

Cable protection systems




| Product Ref. | Nominal Size* [mm] | Length per mini-reel [m] |
|---------------|--------------------|--------------------------|
| CPS05W-150-EU | 5 | 150 |
| CPS08W-100-EU | 8 | 100 |
| CPS13W-50-EU | 13 | 50 |
| CPS19W-25-EU | 19 | 25 |
| CPS25W-25-EU | 25 | 25 |
| CPS29W-15-EU | 29 | 15 |
| CPS32W-15-EU | 32 | 15 |
| CPS38W-15-EU | 38 | 15 |

- Offers excellent protection for cable assemblies against abrasion
- No heat is required to seal the ends of this product as with traditional braided sleeving
- With its wrap-around design, it can be installed on assemblies where the wires are already terminated or wires need to be broken-out
- Bind-It® is available in nominal sizes from 5 mm to 38 mm

Technical Information

| | |
|------------------------------|---|
| Material | Mono and multifilaments of polyester |
| Temperature range | -70°C to +125°C |
| Melt temperature | +255°C |
| Automotive temperature class | T3 |
| Colour | Black |
| Flammability rating | Self-extinguishing, type B (FMVSS-302 Test method D45 1333) |
| Abrasion resistance | PSA D44 1722 : R8 |
| Dielectric strength | from 1kVAC |



* Nominal size is determined by wrapping the product around a mandrel of a given size to obtain 90 degrees of overlap (average value).

Wrap-around woven sleeving - Flame retardant

Cable protection systems

| Product Ref. | Nominal Size* [mm] | Length per mini-reel [m] |
|------------------|--------------------|--------------------------|
| CPS05W-150-FR-EU | 5 | 150 |
| CPS08W-100-FR-EU | 8 | 100 |
| CPS13W-50-FR-EU | 13 | 50 |
| CPS19W-25-FR-EU | 19 | 25 |
| CPS25W-25-FR-EU | 25 | 25 |
| CPS29W-15-FR-EU | 29 | 15 |
| CPS32W-15-FR-EU | 32 | 15 |
| CPS38W-15-FR-EU | 38 | 15 |
| CPS50W-15-FR-EU | 50 | 15 |

- Wrap-around sleeving manufactured from flame-retardant polyester monofilaments and multifilaments
- Designed for mechanical protection and maintenance of wire and cable bundles
- Its construction with 100% covering ratio provides excellent cut-through and abrasion resistance
- No heat is required to seal the ends of this product as with traditional braided sleeving
- With its wrap-around design, it can be installed on assemblies where the wires are already terminated or wires need to be broken-out
- Bind-It® is available in nominal sizes from 5 mm to 50 mm

Technical Information

| | |
|------------------------------|---|
| Material | Mono and multifilaments of polyester |
| Temperature range | -50°C to +125°C |
| Melt temperature | +240°C |
| Automotive temperature class | T3 |
| Colour | Black |
| Flammability rating | Flame retardant (I3-F1), NF16-101 |
| Ignitability test | According to NF-EN-ISO 11925-2 |
| Abrasion resistance | PSA D44 1722: R8 |
| Smoke opacity | NFX 10-702-1; 10-702-2: Pass; Smoke index: 12 |
| Index oxygen | According to NF-ISO 4589-2; OI=36,9 % |
| Dielectric strength | from 1kVAC |
| Other properties | Halogen free |



Product Ref. WT-HSG